

Safety Data Sheet
ADESILEX PG 1 /B

Safety Data Sheet dated: 14/06/2022 - version 5



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ADESILEX PG 1 /B

Trade code: 900571

UFI: SQN0-W0V6-G001-2CFS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Hardener for epoxy products

Uses advised against: Data not available.

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road
Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Corr. 1B Causes severe skin burns and eye damage.
Eye Dam. 1 Causes serious eye damage.
Skin Sens. 1A May cause an allergic skin reaction.
Repr. 2 Suspected of damaging fertility or the unborn child.
Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:
No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P280 Wear protective gloves/clothing and eye/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
3
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
8
P310 Immediately call a POISON CENTER.

P391 Collect spillage.

Special Provisions:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

trimethylhexane-1,6-diamine

m-xylylenediamine

4-tert-butylphenol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%:

Component	Ident. Numb.	Quantity	Material Properties
4-tert-butylphenol	CAS: 98-54-4 - EINECS: 202-679-0 - 67-548-EC: 604-090-00-8	>=2.5 - <5 %	SVHC – Endocrine disruptor

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: ADESILEX PG 1 /B

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number	Material Properties
≥10 - <20 %	m-xylylenediamine	CAS:1477-55-0 EC:216-032-5	Acute Tox. 4, H332; Acute Tox. 4, H302; Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH071	01-2119480150-50	
≥2.5 - <5 %	4-tert-butylphenol	CAS:98-54-4 EC:202-679-0 Index:604-090-00-8	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Chronic 1, H410; Repr. 2, H361f, M-Chronic:1	01-2119489419-21-XXXX	SVHC Endocrine disruptor
≥1 - <2.5 %	Phenol, styrenated	CAS:61788-44-1 EC:262-975-0	Aquatic Chronic 2, H411; Aquatic Acute 1, H400	01-2119979575-18-XXXX	
≥1 - <2.5 %	trimethylhexane-1,6-diamine	CAS:25620-58-0 EC:247-134-8	Acute Tox. 4, H302; Skin Corr. 1C, H314; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	01-2119560598-25-xxxx	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

- Eye irritation
- Eye damages
- Skin Irritation
- Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Ceiling	Long Term mg/m ³	Long Term ppm	Short Term mg/m ³	Short Term ppm	Notes
m-xylenylenediamine CAS: 1477-55-0	ACGIH		C			0,100		Skin - Eye, skin, and GI
		National FINLAND				0,1		FINLAND, takvärde, hud
		National NORWAY	C			0,1		T: Ceiling value is an instantaneous value that

the maximum concentration of the chemical in the breathing zone that should not be exceeded

National AUSTRIA		0,1		0,100	
ACGIH	C			0,1	
ACGIH					Skin - potential significant contribution to overall exposure via the cutaneous route; eye, gastrointestinal and skin irritation
National FRANCE				0,100	
National DENMARK	C			0,1	0,020
National FINLAND	C			0,1	
Malaysian OEL	MALAYSIA				Skin notation
Malaysian OEL	MALAYSIA	C		0,100	
National PORTUGAL	C			0,1	
National SLOVENIA		0,100			
National NORWAY	C			0,1	
DFG	GERMANY	C		1,0	0,16
National DENMARK		0,5	0,08		
National GERMANY		0,5	0,08		
CHE	SWITZERLAND			1	0,16
National SLOVENIA		0,5	0,08	2	0,32
National SLOVAKIA		0,08			

4-tert-butylphenol
CAS: 98-54-4

Predicted No Effect Concentration (PNEC) values

	PNEC Limit	Exposure Route	Exposure Frequency	Remark
m-xylylenediamine CAS: 1477-55-0	0,094 mg/kg	Fresh Water		
	0,0094 mg/l	Marine water		
	0,43 mg/kg	Freshwater sediments		
	0,043 mg/kg	Marine water sediments		
	0,152 mg/l	Intermittent release		
	0,045 mg/kg	Soil		
	10 mg/l	Microorganisms in sewage treatments		
Phenol, styrenated CAS: 61788-44-1	0,001 mg/l	Fresh Water		
	65778 mg/kg	Marine water sediments		
	65778 mg/kg	Freshwater sediments		
	0,17 mg/l	Microorganisms in sewage treatments		
	31525 mg/kg	Soil		

Derived No Effect Level (DNEL) values

	Worker Industr y	Worker Profess ional	Consu mer	Exposure Route	Exposure Frequency	Remark
m-xylylenediamine CAS: 1477-55-0	0,33 mg/kg			Human Dermal		Long Term, systemic effects
	1,2 mg/m3			Human Inhalation		Long Term, systemic effects
	0,2 mg/m3			Human Inhalation		Long Term, local effects
Phenol, styrenated CAS: 61788-44-1	11,02 mg/m3		2,717 mg/m3	Human Inhalation		Long Term, systemic effects
	6,25 mg/kg		3,125 mg/kg	Human Dermal		Long Term, systemic effects
			1,562 mg/kg	Human Oral		Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Nitrile rubber - NBR: thickness $\geq 0,35$ mm; breakthrough time ≥ 480 min.

Butyl rubber - IIR: thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Fluorinated rubber - FKM: thickness $\geq 0,4$ mm; breakthrough time ≥ 480 min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Appearance: paste

Colour: white

Odour: ammonia

Odour threshold: Not available

Melting point / freezing point: Not available

Initial boiling point and boiling range: Not available

Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: 100 °C (212 °F)

Auto-ignition temperature: Not available

Decomposition temperature: Not available

pH: 11.00

Viscosity: 100,000.00 cPs

Kinematic viscosity: Not available

Solubility in water: partly soluble

Solubility in oil: insoluble

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available

Relative density: 1.55 g/cm³

Vapour density: Not available

Particle characteristics:

Particle size: Not available

9.2. Other information

Miscibility: Not available

Conductivity: Not available

Explosive properties: ==

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Corr. 1B(H314)
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Repr. 2(H361)
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

m-xylylenediamine	a) acute toxicity	LD50 Oral Mouse = 930 mg/kg LD50 Skin Rabbit = 2000 mg/kg LC50 Inhalation Mist Rat = 1,34 mg/l 4h LC50 Inhalation Rat = 700, ppm 1h
4-tert-butylphenol	a) acute toxicity	LD50 Skin Rabbit = 2318 mg/kg LD50 Oral Rat = 4000 mg/kg
Phenol, styrenated	a) acute toxicity	LC50 Inhalation Vapour Mouse = 158,3 mg/l 4h LD50 Oral Rat > 2500 mg/kg LD50 Skin Rat > 2000 mg/kg LD50 Skin Rabbit > 7940 mg/kg

LC50 Inhalation Rat > 2,5 mg/l 6h

LD50 Oral Rat 2100 mg/kg

trimethylhexane-1,6-diamine a) acute toxicity

LD50 Oral Rat = 910 mg/kg

11.2. Information on other hazards

Endocrine disrupting properties:

N.A.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
m-xylolenediamine	CAS: 1477-55-0 - EINECS: 216-032-5	a) Aquatic acute toxicity : EC50 Algae = 20 mg/L 72h a) Aquatic acute toxicity : EC50 Daphnia = 15,2 mg/L 48h
4-tert-butylphenol	CAS: 98-54-4 - EINECS: 202-679-0 - INDEX: 604-090-00-8	a) Aquatic acute toxicity : LC50 Fish Oryzias latipes = 87,6 mg/L 96h ECHA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 4,71 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 6,9 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 3,9 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 3,4 mg/L 48h EPA a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 11,2 mg/L 72h IUCLID
Phenol, styrenated	CAS: 61788-44-1 - EINECS: 262-975-0	a) Aquatic acute toxicity : EC50 Daphnia = 4,6 mg/L 48 a) Aquatic acute toxicity : EC50 Algae = 9,7 mg/L 72 a) Aquatic acute toxicity : LC50 Fish = 5,6 mg/L 96
trimethylhexane-1,6-diamine	CAS: 25620-58-0 - EINECS: 247-134-8	a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 29,5 mg/L 72h IUCLID

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%:

Component	Ident. Numb.	Quantity	Material Properties
4-tert-butylphenol	CAS: 98-54-4 - EINECS: 202-679-0 - 67-548-EC: 604-090-00-8	>=2.5 - <5 %	SVHC – Endocrine disruptor

12.6. Endocrine disrupting properties

N.A.

12.7. Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

14.1. UN number or ID number

2735

14.2. UN proper shipping name

ADR-Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-xylylendiamine - paratertiarybutylphenol)

IATA-Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-xylylendiamine - paratertiarybutylphenol)

IMDG-Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-xylylendiamine - paratertiarybutylphenol)

14.3. Transport hazard class(es)

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

14.5. Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Yes

IMDG-EMS: F-A, S-B

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR exempt: No

ADR-Label: 8

ADR-Hazard identification number: 80

ADR-Special Provisions: 274

ADR-Transport category (Tunnel restriction code): 2 (E)

Air (IATA):

IATA-Passenger Aircraft: 851

IATA-Cargo Aircraft: 855

IATA-Label: 8

IATA-Subsidiary hazards: -

IATA-Erg: 8L

IATA-Special Provisions: A3 A803

Sea (IMDG):

IMDG-Stowage and handling: Category A

IMDG-Segregation: SG35

IMDG-Subsidiary hazards: -
IMDG-Special Provisions: 274
IMDG-EMS: F-A, S-B

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC) : N.A. g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1 **Lower-tier threshold (tonnes)** **Upper-tier threshold (tonnes)**

Product belongs to category: E2 200 500

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

SVHC Substances:

Substances in candidate list (Art. 59 Reg. 1907/2006, REACH):

Component	Ident. Numb.	Quantity	Material Properties
4-tert-butylphenol	CAS: 98-54-4	>=2.5 - <5 %	SVHC
	EINECS: 202-679-0		Endocrine disruptor
	Index: 604-090-00-8		

National regulations

Produktregisteret Norge: 110822

Produktregistret Sverige: 658461-9

Produktregister Danmark: 4147027

MAL-kode: 00-5 (1993) A+B: 5-5 (1993)

German Water Hazard Class.

2

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
EUH071	Corrosive to the respiratory tract.
H302	Harmful if swallowed.

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.7/2	Repr. 2	Reproductive toxicity, Category 2
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
3.2/1B	Calculation method
3.3/1	Calculation method
3.4.2/1A	Calculation method
3.7/2	Calculation method
4.1/C2	Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.
CMR: Carcinogenic, Mutagenic and Reprotoxic
COD: Chemical Oxygen Demand
COV: Volatile Organic Compound
CSA: Chemical Safety Assessment
CSR: Chemical Safety Report
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level.
DPD: Dangerous Preparations Directive
DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: KAFH
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

*** Sheet model entirely changed in compliance to regulatory update.**